

NCR EasyPoint™ 62

Looking for a reliable ATM with flexible placement opportunities?

YES

Attract more customers in more locations

NCR EasyPoint 62 is a small footprint free-standing interior cash dispenser that offers very low total cost of ownership, resulting in more profitable deployments, even at lower transaction volumes. Ideal for retail locations, NCR EasyPoint 62 attracts more customers and increases store traffic and sales by offering a range of services that can create direct income through transaction fees.

- **Reduces energy costs**

Using NCR's Intelligent Power Management system, NCR EasyPoint 62 is safeguarded in the event of a power failure by enabling transaction completion, as well as enabling significant reductions in energy consumption, so you can reduce costs while helping the environment.

- **Security your customers can trust**

NCR EasyPoint 62 maintains the integrity of your self-service channel for you and your customers by incorporating security features, including countermeasures to ATM fraud, Encrypting PIN Pad, support for EMV, Triple DES and Remote Key Management.

- **Quick and flexible installation**

With a small footprint, minimal infrastructure requirements and enhanced environmental capabilities, NCR EasyPoint 62 is very easy and fast to install in a wide range of locations.

- **Effortless integration with your network**

NCR EasyPoint 62 can easily be integrated with the rest of your network. Because it operates a Windows® XP platform using NCR's APTRA™ software, you can run common applications across your network that provide consistent branding and messaging.

- **Reach more customers**

Customer attraction and interaction is maximized by NCR EasyPoint 62's large screen, which supports complex graphically intense transactions, advertising and customer guidance using graphical or animated instructions.



For more information, visit www.ncr.com,
or email financial@ncr.com.

Key Features

- Encrypting PIN Pad
- 12.1" color LCD screen
- Card reader with built-in fraud prevention
- Wireless communication support
- Dust filtration system
- Optional privacy screens and convenience shelves

Why NCR?

With over 125 years of experience and knowledge, NCR is the leading global provider of payments, assisted- and self-service solutions. NCR has been the global number one manufacturer of ATMs for more than 22 consecutive years. We help our clients around the world improve their customer interactions, implement change quickly and proactively, and transform their businesses to become leaders and change agents. We can help you, too.

Technical Specifications

PRODUCT DIMENSIONS

HEIGHT 56.6" (1,438mm)

WIDTH

With convenience shelves 32.5" (825mm)

Without convenience shelves 18.5" (470mm)

DEPTH

With convenience shelves 29.7" (755mm)

Without convenience shelves 27.5" (698mm)

With privacy wings 29.7" (755mm)

Without privacy wings 27.5" (698mm)

WEIGHT

UL 291 Level 1 770lbs (350kg)

Business hours safe 550lbs (250kg)

CUSTOMER INTERFACE

- Display – 12.1" (308mm) XGA standard color
- LCD with autoscaling capability, 8 tactile function display keys
- Keyboard – EPP: supports Triple DES and Remote Key Management
- Card reader – Smart Dip, IMCRW with smart option
- Integrated Media Entry and Exit Indicators (MEEI)
- Audio - Sound jack with volume control

DISPENSER

- 1, 2 or 3 denominations, spray presenter

PRINTER

- Receipt printer – 60mm graphics thermal printer or 80mm graphics thermal printer
- Journal Printer – 40 column graphics thermal printer

SECURITY

- Options – Fraudulent Device Inhibitor, Enhanced Card Drive, Illuminated MEEI in the card reader throat, privacy wings, alarms
- Safes – UL 291 Level 1 construction safe, UL 291 business hours

COMMUNICATION OPTIONS

- Dial-up, TCP/IP, leased line, wireless communications enabled, integrated ethernet

ENVIRONMENTAL

- Level 1 dust filtration
- Optional Level 2 dust filtration
- Optional Level 3 dust filtration
- Temperature – 50°F to 104°F (10°C to 40°C)
- Humidity – 20% to 80%
- Acoustics – Sound power 65dBA idle, 68dBA operating, sound pressure 65dBA operating
- Power requirements
 - 120V 50Hz to 60Hz
 - 220V to 240V 50Hz to 60Hz

OPERATING PLATFORM

- Intel® Pentium® 4
- CD-ROM or DVD-ROM

SOFTWARE

- Windows® XP
- APTRA software suite

ADDITIONAL FEATURES

- NCR Intelligent Power Management
- Convenience shelves
- Electronic journal



Experience a new world of interaction

NCR EasyPoint 62

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR EasyPoint and APTRA are either registered trademarks or trademarks of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.

© 2008 NCR Corporation Patents Pending

EB5836-0908

www.ncr.com