

# RT2000



## *Finally, get more out of your high-traffic location with a cost efficient, 24-hour, through-the-wall ATM.*

For many high-traffic locations, there has simply never been a cost-effective way to provide customers with access to a 24-hour walk-up ATM. Most of the big, traditional ATMs are too costly and complicated to even consider. The extremely reliable and affordable RT2000 gives merchants a low-cost, easy to service alternative to more expensive through-the-wall ATMs.

The RT2000 boasts viewing options not available elsewhere in the market. Bigger display options and the ability to keep sunlight at bay make this ATM the choice for outdoor placement.

It's no surprise this innovation comes from Triton. Triton customers know that our hallmark affordability is the result of decades of engineering and innovation. The RT2000's high-performance is partly

due to the Triton custom-engineered dispensing mechanisms. Triton's self-calibrating dispenser mechanisms are designed to dispense 250,000 notes with no preventive maintenance.

The Triton RT2000 is easy to install. It's easy to maintain. And most of all, its low cost and reliability mean your high-traffic ATM location can finally become a high-profit ATM location. Finally. A through-the-wall ATM built by the experts in retail ATMs.

 **Triton**  
WHERE MONEY COMES FROM.®  
A  DOVER COMPANY



# RT2000

In Detail

*A cost-efficient, 24-hour, through-the-wall ATM designed with the merchant in mind.*

## FEATURES:

- Multi-cassette standard
- 10.4" (264 mm) color display with 640 x 480 resolution and sunlight readable LCD
- Optional rear service panel with touch screen display
- 80 mm thermal printer with presenter
- 64 MB RAM, expandable
- 2 MB journal storage (32,768 records)
- Triton Connect™ compatible
- Dip-style card reader, optional dip EMV smart card reader; optional EMV motorized card reader (Track 1,2,3 Read), or EMV motorized card reader/encoder (Track 1,2,3 Read, Track 3 write)
- Americans with Disabilities Act (ADA) and audio compliant
- Encrypting PIN Pad (EPP) to comply with all international encryption standards, PCI compliant
- UL 291 Business Hours cabinet; optional UL 291 Level 1 Safe
- Manual lock, optional electronic lock or Kaba® Mas Cencen lock
- Multi-lingual capabilities
- Dial-up 56k baud internationally certified modem and TCP/IP communications standard
- LED lead-through indicators
- Dimensions:
  - Depth: 29.7" (754 mm)
  - for walls as thick as 11" (279 mm)

- Width: 20.5" (521 mm); 22.4" (569 mm) Sleeve
- Height: 63.6" (1615 mm)
- Weight: 275 lbs (125 kg) *weight varies with options*
- Advertising revenue potential:
  - Decals and signage
  - Couponing
  - Display graphics

## TECHNICAL SPECS:

- RISC microprocessor
- Microsoft Windows® CE 5.0
- 128 MB flash memory, expandable
- Six USB master ports
- One compact FLASH socket
- Five serial ports


## OPERATING SPECS:

- Temperature:
  - Vault/Electronics: 50° to 104° F (10° to 40° C)
  - External: -30° to 122° F (-35° to 50° C)
- Relative humidity:
  - 20% to 80% non-condensing
- Power consumption:
  - 2.0 A @ 115 VAC at 60 Hz
  - 1.0 A @ 230 VAC at 50 Hz

Triton Headquarters • 522 East Railroad Street  
Long Beach, Mississippi 39560 USA  
With offices throughout the U.S. and worldwide including Canada, UK, Australia, and Hong Kong  
Phone: 1-228-868-1317 • Toll free: USA & Canada 1-800-367-7191  
www.triton.com • Email: sales@triton.com

© 2008 Delaware Capital Formation, Inc. All Rights Reserved. TRITON, TRITON WHERE MONEY COMES FROM, DOVER and DOVER logo are registered trademarks of Delaware Capital Formation, Inc., a wholly-owned subsidiary of Dover Corporation.

Current as of 2/08 -RT2000 product sheet-07203-00121



*The dimensions shown comply with U.S. Federal ADA guidelines. For installation within the U.S., be sure to check state and local guidelines for complete compliance. For non-USA installations, check regulations for the country in which the machine will be installed.*

*\*specifications subject to change without notice*

ATM INSTALLATION SPACE REQUIREMENTS FOR ADA COMPLIANCE